TIMAK

FIREFIGHTING

SUPPORT TANKER

Efficiency in fire management and disaster response means rescuing people faster, improving the way fires are extinguished, providing more effective protection and ensuring more reliable recovery operations.





Notes: Images are for illustrative purposes only and may appear different to the actual vehicle.

TECHNICAL SPECIFICATIONS

Standard Features

Chassis	4x2 - 6x2- 6x4 - 8x2 - 8x4		
Bodywork	Modular		
Water tank	6.000–18.000 liters stainless steel		
Foam Tank	150-500 liters stainless steel		
Pump Capacity (Lt / min)	TMK 1500 N 1.500 l/m at 10 bar	TMK 3000 NH 2.000 l/m at 10 bar 250 l/m at 40 bar	TMK 4000 N 4.000 l/m at 10 bar
Drive	PTO	PTO	PTO
Foam Rationing	Around the pump 3% - 6%	Around the pump 3% - 6%	Around the pump 3% - 6%
Monitor	TMK - 1200	TMK - 2400	TMK - 3000
Capacity (Lt / min)	1200	2400	3000
Control	Manual	Manual	Manual
Front Irrigation System	Pre-pressurized type, free flow type at the rear		
Lighting Warning	Lightbar with Siren System Interior Lighting 2 Fixed Projectors		
First Responders Hose Reel	1 unit		
Operation	Manual Unwinding – Electrical Rewinding		
Hose	1" x 50m		
Nozzle	Jet / Fog Pistol		
Accessories	Standard Accessories Available		

