TIMAK

CANAL JETTING VEHICLE

TIMAK pressure/vacuum trucks are perfect for day-to-day suction, discharge and transportation activities, general industrial cleaning or for use in the (petro)chemical industry and in refineries.





TECHNICAL SPECIFICATIONS

Standard Features

Туре	Canal Jetting Vehicle
Tank Volume	3.000 lt. – 10.000 lt.
Clean Water Tank Material	304 & 316 Cr-Ni
Tail Gate	Full hydraulic
Water pump	100 bar – 250 bar
Pump Flowrate	150 lt/dk. – 425 lt/dk.
Pressure regulator	Pneumatic
Main Hose Reel	Hydraulic 60-200 mt. Hose Length
Secondary Hose Reel	Manual or Hydraulic 60-100 mt. Hose Length
Manhole/Wheel Lifting Crane	250 & 400 kg. capacity

Standard Accessories

2 Cylindrical Rotating Lamps

1 Coupling Spanners

1 Projector

1 Egg Type Channel Opening Nozzle

1 Oval Type Channel Opening Nozzle

Optional Accessories

Stainless Steel Tank

Hydraulic Electric Crane

High Pressure Pump up to 300 Lt / min Capacity at 200 bar

Drum Swivel Feature Up to 135°

Remote Controlled Monitor

Hydraulic Auxiliary Hose Reel

